

KAMPEL WoodFil® EPOXY

REPAIR AND REBUILD WOOD FAST AND EASY

*for the
Finishing
Touch!*



KAMPEL
ENTERPRISES, INCORPORATED
www.kampelent.com

K A M P E L

HOW TO USE KAMPEL WOODFIL EPOXY



- Using a pocket knife or utility knife, cut off the desired amount of WoodFil Epoxy.
- Knead the product until the color is uniform, then apply the mixed WoodFil Epoxy to the object that's being repaired.

Strength & Versatility

WoodFil Epoxy is a two-part, hand mixable epoxy putty used to rebuild and repair real wood. WoodFil Epoxy's strength and versatility is what makes it unique. Unlike most wood putty, WoodFil Epoxy has similar strength to the real wood that is being repaired.

The product adheres to a component, cures hard, and makes an extremely durable repair. WoodFil Epoxy may be machined, threaded, filed, sanded, stained and painted. WoodFil Epoxy does not shrink, completely filling the defect or damaged area.

Common Uses

- Repair gouges, dry rot, knotholes and cracks in flooring and countertops
- Rebuild broken cabinet corners, edges and molding
- Repair mis-drilled holes in cabinet doors

Work-Life

Depending on the color, WoodFil Epoxy has a 3-5 minute or 15-25 minute work-life and is completely cured after 60 minutes.

Changing its Color

Mixing different colored sticks of WoodFil Epoxy will allow you to create new colors that match your wood grain. Stain may be mixed into WoodFil Epoxy to alter its color before it cures by kneading stain into the product. Stain may also be applied to cured WoodFil Epoxy.

KAMPEL WoodFil EPOXY

REPAIR AND REBUILD WOOD FAST AND EASY

WoodFil Epoxy is available in five distinct wood colors and white.




Walnut



Maple



Oak



Cherry



Pine



White

APPLICATION

Repairing A Mis-Drilled Pocket Hinge Hole

Press the just mixed WoodFil Epoxy into the hole drilled off location, completely filling void.



After 60 minutes sand excess cured WoodFil Epoxy from repaired area and stain if necessary.



Re-drill hole in correct location, machining directly into cured WoodFil Epoxy.



Attach pocket hinge to correct location, threading screw directly into cured WoodFil Epoxy.



KAMPEL

ENTERPRISES, INCORPORATED

P.O. BOX 157, WELLSVILLE, PA 17365-0157
PHONE: 800-837-4971 FAX: 800-778-7006
Visit us on the web: www.kampelent.com